

URANIA LD9 Cod. 1356

DESCRIPTION

High performance lubricant developed with IVECO and FPT for Euro V and Euro VI engines fitted with HI-eSCR system, common rail injection, particulate filter and variable geometry turbine. Its low SAPS formulation offers high protection for the particulate filter against combustion residues.

It exceeds IVECO 18-1804 CLASSE TLS E9, C.T.R. I720.I12

CHARACTERISTICS

Urania LD9 has been developed in co-engineering with IVECO and FPT and exceeds the latest international standards.

Its formulation obtained with sulphur free base oil offers:

- | high protection of the particulate filter;
- | improves cleanliness and protection of the engine;
- | high performance of the variable geometry turbine under harsh operating conditions;
- | excellent Fuel Economy;

ADVICE ON USE

IVECO recommends the use of Urania LD9 for CURSOR and TECTOR engines, in particular for Euro V and Euro VI engines fitted with Hi-eSCR system.

RECOMMENDED BY

IVECO

TECHNICAL DATA

SAE 10W-40, API CJ-4/SM, ACEA E7/E9,
IVECO STANDARD 18-1804 CLASSE TLS E9, CONTRACTUAL TECHNICAL REF. N°1109.L12,
CAT ECF-3/ECF-2/ECF-1a, CUMMINS CES 20081,
DETROIT DIESEL 93K218, DEUTZ DQC III-10-LA,
DAF: Suitable for normal drain intervals and engines equipped with DPF.,
MACK EO-O PREMIUM PLUS-07, MAN M3575,
MB-Approval 228.31, MTU OIL TYPE 2.1,
RENAULT RVI RLD-3,
Scania: Suitable for normal oil change intervals and engines with DPF.,
VOLVO VDS-4

